

Superior Chemistry. Superior Performance.



FULL SYNTHETIC ULTRA MULTI-PURPOSE LITHIUM GREASE

FULL SYNTHETIC ULTRA GREASE

MAG 1 Ultra Grease is specially formulated with a premium, 100% full synthetic PAO. This lithium complex grease provides excellent oxidation resistance and thermal stability at high temperatures while providing excellent low temperature pumpability and excellent wear protection for longer equipment life. This grease has high film strength, extreme pressure (EP) protection and, anti-wear properties. NLGI Grade # 2.

PERFORMANCE PROPERTIES INCLUDE:

- EP (Extreme pressure) protection
- Dropping point in excess of 500° F
- Low temperature protection -40°F
- Excellent water wash out protection
- GC-LB rated chassis lube

RECOMMENDED FOR THE FOLLOWING APPLICATIONS:

- Bearings for passenger cars, trucks and mobile equipment
- Chassis/Suspension parts
- Boats, Trailers, marine applications
- Construction equipment, agricultural equipment, off highway construction equipment, logging and forestry equipment



**Typical Physical Properties of MAG 1®
Full Synthetic Ultra Multi-Purpose Grease**

	Test Type	Results
Viscosity @ 100°C cSt	ASTM D 445	20-25
Viscosity @ 40°C cSt	ASTM D 445	210-230
Viscosity Index	ASTM D 445	140
Oil Separation, 24 hours @ 77°F	ASTM D 1742	10
Timken	ASTM D 2509	55
Color	NA	Purple
Dropping Point, °F (°C)	ASTM D 2265	265-295

Description	Stock # / Order #	Each UPC	Case UPC / Shipping UPC	Case Dimensions	Case Cube / Pallet Cube	Case Weight / Pallet Weight	Pallet Stack
FS Ultra Multi-Purpose Grease 10/14 oz	64049 MG680014	0 71621-64049 4	0 71621-64051 7 1 00 71621-64049 1	L 11.500 x W 9.980 x H 9.750	0.308 / 62.708	9.980 / 1547.000	300 Cases (5 layers of 30)

