



Pioneer Premiere Unitran ATF

Applications

Pioneer Premiere Unitran ATF is manufactured to stringent new vehicle manufacturers' specifications from premium quality paraffinic base oils blended with a specifically balanced additive combination to provide high oxidation stability, excellent foam resistance, corrosion and wear protection, and heat resistance. This complex fluid is also compounded with a friction-modifying additive to provide smooth lock-up of clutches without chatter. Unitran ATF is a multipurpose fluid that meets and exceeds all current original equipment manufacturers specifications for automatic transmission fluids.

Features

Pioneer Premiere Unitran ATF meets carmaker's warranty requirements. Excellent wear, rust and corrosion protection and quiet, smooth operation. Outstanding seal compatibility and does not degrade nylon components. Superior thermal and oxidation stability.

Pioneer Premiere Unitran ATF meets or exceeds the following specifications:
DEXRON® III, DEXRON® IIE, DEXRON®
MERCON®, Ford ESP-M2C138-CJ, Ford ESP-M2C166-H
Type A Suffix A, Allison C-3/C-4 and Caterpillar TO-2 fluids.

Typical Specifications

Specific Gravity @ 60°F	0.8616
Viscosity @ 40°C cSt	38.7
Viscosity @ 100°C cSt	7.55
Pour Point °C (°F)	-51°C (-60°F)
Viscosity Index	167
Color	Red
Gravity, °API	32.73
Brookfield Viscosity cP @ 40°C	18,700

PIONEER
D I S T R I B U T I N G C O .

Quality Products * Excellence In Service
Since 1947

1300 North 24th Avenue
Phoenix, AZ 85009-3618

Phone: 602-278-2693
Fax: 602-278-0285
www.pioneerdistributing.com