



Pioneer Premiere Drip Oil 32

Features

Pioneer Premiere Drip Oil 32 is a made from hydrotreated paraffinic base oils. It is an antiwear fluid designed for use as an intermittent drip-type lubricant in irrigation, conveyor and industrial lubricating systems. It protects against rust, oxidation and wear and contains a foam inhibitor.

Typical Specifications

Specific Gravity @ 60°F	0.849
Color	L 0.5
Appearance	Clear & Bright
Viscosity @ 40°C cSt	24.8
Viscosity @ 100°C cSt	4.8
Viscosity Index	113
Flash Point °C (°F)	228 (442)
Pour Point °C (°F)	-18 (-0)
CCS Viscosity at -25°C, cP	1730
CCS Viscosity at -20°C, cP	960
Evaporative Loss, NOACK, wt%	12.5
Volatility @ 371°C, wt%	3.9
Sulfur, µg/g	<300
Polycyclic Aromatics, wt%	< 3.0
Modified Ames Assay	MI < 1

PIONEER
D I S T R I B U T I N G C O .

Quality Products * Excellence In Service
Since 1947

1300 North 24th Avenue
Phoenix, AZ 85009-3618

Phone: 602-278-2693
Fax: 602-278-0285
www.pioneerdistributing.com