



Pioneer Premiere Red Hi-Temp EP #2

Applications

Pioneer Premiere Red Hi-Temp EP #2 Grease is recommended for wheel bearings, fifth wheel, U-Joints, steering linkage and chassis lubrication.

Recommend as a chassis lubricant in both on and off road equipment where severe water washing or shock loading protection is required.

Features

NLGI Service Classification GC-LB.

Premium quality lithium complex multi-purpose grease.

Fully additive treated: EP, antiwear, tackiness adhesives, rust and oxidation inhibited.

Water insoluble with superior water washout resistance and protection against shock loads.

Typical Specifications

NLGI Consistency Number	2
Thickener	Lithium Complex
Texture	Smooth, Adhesive
Color	Red
Worked Penetration @ 77°F	280
Dropping Point, °F	500
Four-Ball Wear, 1200 rpm 40kg, 1 hr @ 75°C	0.56 mm
Timken OK Load, Minimum	70 lb
Base Oil Viscosity cSt @ 40°C	220
Base Oil Viscosity cSt @ 100°C	14.3

PIONEER
D I S T R I B U T I N G C O .

Quality Products * Excellence In Service
Since 1947

1300 North 24th Avenue
Phoenix, AZ 85009-3618

Phone: 602-278-2693
Fax: 602-278-0285
www.pioneerdistributing.com